





ST=P STONE

READY TO INSTALL VITRIFIED STEPS 300×1200 MM STEP | 200×1200 MM RISER











READY TO INSTALL STEPS AND RISERS

Stairs and staircases are not defined by their functionality alone. These practical units are also interesting from a design perspective as well-appointed stairs are today a defining feature in houses, rooms or hallways. Kajaria Step Stone Vitrified Steps and riser comes with different colours and shades, suits to your interior and exterior spaces.

















Highly durable, ideal for heavy traffic and commercial areas, Indoor & Outdoor.

Easy and speedy installation. Say goodbye to cumbersome cutting and finishing on site.

Embossed Tread Lines Provide extra grip for higher safety near step edge. Unique full bull nose edges

Provides higher strength and durability as desired in big size slabs. An assurance to replace natural stones in a confident way. Highest abrasion resistance

Ensures 10 times superior surface protection against wear and tear over natural stones.

Available in 8 beautiful Salt & Pepper shades. Suits the building theme, décor and desired contrast.

Sizes available

teps	300x1200mn
ser	200×1200mn

landing area tile

600x1200mm

READY TO INSTALL VITRIFIED STEPS

SELF EMBOSSED GROOVES

Provides Better Grip

BULL NOSE FINISH

Prevent Injuries from Sharp edges

ANTI SKID PROPERTY

Coefficient of Friction (u >0.4)

FULL BODY VITRIFIED TILES

Homogeneous Body

THICK BODY

Thickness 12 mm (Steps)





FEATURES & BENEFITS

Concepts for Designing

Step Stone by Kajaria are available in different designs and colours. As high-quality tiles, they meet the technical requirements of different standards for the production of stairs. The comprehensive concepts comprising basic, décor and functional tiles can be used for a durable and aesthetically pleasing design of the entire indoor & outdoor stair area.

Safety for Senior Citizens, Physical disables and Children


Safety is always the number-one priority. It is safe enough for senior citizens, physical disables and children. In addition to slip resistance in compliance with the applicable standards, Step Stone Vitrified tiles offer particular durability and also easy-care properties. These full-bodied tiles come with bull nosing and tread lines that make them skid-resistant and much more safer than conventional stairs.

Long Lasting & Easy Maintinance


Step Stone are full-bodied vitrified tiles, which means they absorb very low water and are impervious to weather or wear and tear induced damage. Fit them and forget them for years of trouble free performance.

Easy Installation

No more handling issues. No more labour-intensive on-site installations, no more wastage costs. Kajaria Step Stone can be easily and speedily installed on site. Chipped and worn out staircases, constant need for polishing and repairs, are all things of the past.



Kajaria Step Stone Steps are available in 300x1200mm. These can be used in full size and in cut size as depending on the requirement. While the riser tiles are available in a convenient size of 200x1200mm. For stairs requiring higher width, cut - contrast shades can be used on either side to get the wider stairs.



GRANITE

Variation in Shade, Color, Density

Has to cut in sizes

Bull nosing, Half nosing will need to done

Cut Grooves need to be done

Longer Installation time

High cost

Affected by Weather hot/cold

High Maintenance

STEP STONE

Unpack Box, No Color, Density variation

Ready to Lay Tiles

Ready Bull nose


Ready Emboss grooves

Easy to Install

Lower cost than granite

Impervious to weather

Easy to maintain






















12252 | RISER 200x1200MM




















12253 | RISER 200x1200MM











12354 | STEP 300x1200MM



12254 | RISER 200x1200MM

















12355 | STEP 300x1200MM



12255 | RISER 200x1200MM












12256 | RISER 200x1200MM
























12358 | STEP 300x1200MM



12258 | RISER 200x1200MM



MATCHING LANDING AREA TILES WITH STEPS & RISER 300x1200 | 200x1200 | 600x1200 MM



200x1200MM 12654 | LANDING AREA TILE

600x1200MM

12254 | RISER



APPLICATION AREAS









INDOOR

OUTDOOR

SWIMMING POOL FIRE EXIT







UNIVERSITY

HOSPITAL

SHOPPING MALL

Recommended Stair Step Dimensions as per National Building Code, BIS, SP:7

Type of Building	Minimum Width	Minimum Tread	Minimum Riser
Residential buildings	1000 mm	250 mm	190 mm
Residential hotel buildings	1500mm	300 mm	150 mm
Assembly buildings like auditoria, theatres and cinemas	2000 mm	300 mm	150 mm
Educational building	1500 mm	300 mm	150 mm
Institutional buildings	2000 mm	300 mm	150 mm
All other buildings	1500mm	300 mm	150 mm
2 storeyed - LIC Urban Areas	600 mm	225 mm	200 mm
3 or more storeyed - LIC Urban Areas	750 mm	250 mm	200 mm

Note: Straight flights of steps are preferred by ambulant disabled people. Steps should be of a consistent height and depth throughout the stair. Stairs shall be constructed of non-combustible materials throughout.



TECHNICAL SPECIFICATION - FULL BODY VITRIFIED TILES

S. Ho.	CHARACTERISTIC	International Standards Group Baa- ISO 13006 Annx. G.	MEAN VALUE OF KAJARIA	TEST METHOD
	Dimensions & surface Quality		0 0	
1.	Deviation in length and width	± 0.6%	+ 0.1%	150 105452
2	Deviation in thickness	F5%	±.4%()	150:105452
3.	Deviation in Straightness of sides	± 0.5%	10.1%	ISO 10545'2
4.	Deviation in Rectangualrity	± 0.6%	×0.3%	150 105452
5	Deviation in Surface Flatness	105%	102%	150 105452
6.	Surface Quality (10)	Minimum 95%	No visible defects	ISO 105452
	Physical characterattics			
7.	Scratch Hardness of surface Moh's scale	Min. 6	Min. 6	ISO 10545'3
8.	Water absorption	+ 0.5%	# 0.05%	ISO 105453
9.	Moisture Expansion	NII	NIL	(\$0 :054510
10.	Surface Abrusion Resistance	max x75mm ¹	e 144mm ¹	ISO 105457
	Mechanical characterritics			
71.	Breaking strength	1300 n	± 2200 ft	150 205454
12	Modulus of rupture	≥ 35 N/mm²	a 35 M/mm²	150 105454
18.	Impact resistance	Declared by manufacturer	no indientation or cracking	150 10545/5
	Safety charactersiticsDensity			
14.	Density	220 gm/cc	2:34 gm/oc	DIN 51082
15.	Sleid resistance	it it	More than Rso (60x60cm x 9.7mm)	DIN 51130
	Thermo photo charactersitics			
16	Thermal shock resistance	Resistant to 10 cycles	Pass min 30 cycles	150 1054519
17,	Co efficient of thermal expunsion	gkt0"K"Max	etikito"k"Max	ISO 10645/8
18.	Frost resistance	Resistant	Resistant	ISO x054532
19.	Color Resistance to UV light	Resistant	Resistant	150 1054515
	Chemical characteristics characteristics			
20	Stain Resistance	Resistant	Registant	150 2054514
21	Chemical Resistance House Hours One HICAL & SWIMMENG POOL SAU	min class-UB	Conform to classes-LIA	150 1054513
22	Chemical Resistance LOW CONCENTRATIONS ACCES ALVALIES	min class-ULB	Conform to classes-ULA	150 1054513
23.	Chemical Resistance HOH CONCENTRATIONS ACID & ALKAUES	min class-ULB	Conform to classes-UHA	ISO 10545:13

PACKING DETAILS

5. No.	Dimensions (mm)	No. of tiles / box	Coverage Area
1	200x200	n Pcs	1.44 Sq. Httl
2.	\$00KI200	A Pos.	1.44 Sq. Mtr.
3	600x1200	2 Pcs.	1.44 Sq. Mir

^{*} Vitrified tiles have resistance to most of the stains/chemicals but it is recommended to take due care while laying and for day-to-day maintenance

- 1. Colours in the catalog are as accurate as printing process allows
- 2. Sizes mentioned in the catalog are the nominal sizes only.
- 3. Conforming to ISO requirements, technical specifications for Kajaria tiles are applicable only for 1st quality tiles.
- 4. Please inspect all tiles prior to installation; company will not entertain complaints, once tiles are laid / fixed.
- 5. For better laying, please follow the instructions on the packaging box.

[#] Resistance to acids & alkalies (Exception Hydrofluoric Acids & its Compounds)



Frequently Asked Questions

Why Kajaria Step Stone is the new benchmark in the world of staircases?:

Natural stones have been the mainstay of staircases. These stones are not easy to install and are slippery. Moreover, due to lack of uniformity in size, there is a higher wastage cost. Kajaria Step Stone is a revolutionary tile which sidesteps all the complications associated with natural stones. Also, Kajaria Step Stones comes in a convenient size of 300x1200 mm Step with bull nosing and tread lines, 200x1200 mm Riser and 600x1200 mm Landing area tiles in matching colour. This size ensures it meets the design requirements of most staircases.

How Kajaria Step Stone is different from others?

Safety and durability are the cornerstones of Kajaria Step Stone. As a full-bodied Vitrified Tile, it encompasses a high degree of strength with antiskid and stain resistant properties, which makes it a safe and excellent choice, especially for people with ambulant disabilities.

What are the advantages of full bull nose edges?

Kajaria Step Stone is a Full body Bull Nosed vitrified step tile. The unique bull nosing makes the staircase safer and comfortable to step on. It also helps to prevent chipping along edges and gives the staircase an aesthetically pleasing look.

What is the purpose of embossed tread lines?

The embossed tread lines provide extra grip when stepped on, especially near the edges of the steps. This ensures higher safety, preventing people from falling down and risking injuries.

What are the benefits of thicker tiles?

For staircases, it makes sense to have strong tiles which Kajaria Step Stone is owing to its thickness. It ensures safety, lends confidence and assures replacement to natural stones.

What are the other benefits of using Kajaria Step Stone?

The ease and speed of installation, low water absorption (<0.05%) with advanced stain resistance technology. Also due to its high abrasion resistance it provides 10 times more surface protection than natural stones.



NORTH

CHANDIGARH

SCO- 45-46-47, first floor, sector-17A, opp. Taj Hotel, Chandigarh-160017 Muble: 9779042134, 9779009264 Phone: 0172-4631419 / 16

DELHI

J-1/B-1 (Extn.), Mohan Co-Operative Industrial Estata, (Opp. Baderpur Thermal Power Station), Mathura Road, New Delhi - 110 044. (Delhi) Mobile : 9717795123, 9717795181

DEHRADUN

International Trade Tower, 1 Old Survey Road, Adjoining Rejour Road,, Near Cross Road Mail Dehradun - 248001, Ultarakhand Mobile : 97600 40499

JAIPUR

G-1-2, Ashwarya Tower Near Hotel Haws Mahal, Ajmer Ruad, Jaiour-302005, (Rajesthan) Mobile : 9929022124

LUDHIANA

Upper Ground Floor, Sandhu Tower-2, Gurdev Nagar, Ferozpur Road. Ludhiane - 141001, Punish Mobile : 9779021257

LUCKNOW

529 GHA/06, Kanchana Bihari Marg, Near Jagrani Hospital, Ring Road Lucknow - 226016 (U.P.) Mobile: 9793299660, 8173001374

VARANASI

Rukmani Tower, N8/247-2K-1, DLW. BHU Road, Newada, Sunderpur Varenesi 221005, Littar Predesit Mobile : 9794865554, 9005065656

SOUTH

HANGALORE

Farah loon, 119 First Floor Opp. New Pass Port Kendra, Lalbagh Rusq. Bangalore - 560 027, (Karnatika) Mobile : 9008098325, 9008007336, 90082 78672

Old No 121 New No 38 Arrhant lashin Building: Ruhman Lakshmipathi Salai, Opp to Rajarathinam Stadium, Egmore Chennal - 600008, TamilNadu Mobile : 9003077099 Phone: 044-28594990 / 28594991

COCHIN

MN Square, 1st Floor 549/2, Near Gold Souk Grande NH Bypess, Willie, Cochin. 19, (Kerale) Mobile: 9746474732, 9746474739, 9746474733

COIMBATORE

First Floor , No.57, Cowley Brown Road. R.S. Puram, Colmbatora - 641002, (Tamii Nadu) Mobile: 9003325075

HYDERARAD

Koerthi & Prido Towers, House No. 8-2-120/86/162, 3rd Floor, plot No.11 & 12, Road No.2, Banjara Hills Hyderabad-500034, (Telangaria) Mobile 9000005385

VI.IAVWADA

61-3/4-1, 1st Road, Geetha Nager, Beside SBI Bank, NH-5, Vijaywada 520013, (Andhra Pradesh) Mobile : 7799660222, 9000302776

WEST

B1 307, BOOMERANG, Chandivali Farm Road, Near Chandivall Studio, Off Saki Viher Read. Andheri (E) Mumbai - 400072, (Mahareshtra) Mobile: 9287753947,9987753948

NAGPUR

Parthamesh Raia Apartment. Above Bank of Barode, Limeshane Road, Medical Square, Nagpur - 440009; (Maharashtra) Mobile: 7755904583

PUNE

601 A. D.S.K. Ganghary Holents. Ganesh Khind Road, Shivaji Nagar, Pune - 411005, (Maharashtra) Mobile: 7028005373

CENTRAL

RAIPUR

1st Floor, Maharaja Plaza, Nesr Wholesale Fruit Market, Dhamtarl Road, Leabur Raipur 492001, Chhattisgarh Mobile : 9755007408

SALES REPRESENTATIVE

NORTH

Mobile: 9760045574

ALLAHABAD | Mobile : 9773983600

внатимов.

Mobile: 9501001162

FARIDABAD I Mobile: 9717219345

Mobile : 9717795118 9650065523

GHAZIABAD :

Mile: 9810010240

GORAKHPUR: Mobile: 8009407878

HALDWANE

Mobile: 9760098112

HISSAR :

Mobile: 9996907982

JALANDHAR :

Mobile: 9779021261

JAMMU :

Mobile : 9906909300

JODHPUR :

Mobile: 9001094759

KANPUR I Mobile: 8173001374

CHAZIABAD/ NOIDA

Mobile : 9810010240

ROHTAK :

Mobile | 9996907982

SHIMLA

Mobile | 9501001163

UDAIPUR -

Mobile : 9001092597

EAST

BIHAR :

Mobile : 7781005449

JHARKHAND :

Mobile : 9938234060

Mobile : 9007372220

Mobile : 9937571222

SOUTH

CALICUT: Mobile : 9746117422

KANNUR : Mobile : 9746474736

HUBLI : Mobile : 9008022099

MADURAL:

Mobile : 9840284411

MANGALORE: Mobile : 9008402944

SALEM | Mubile : 9003842142

TRIVANDURM: Mobile : 9745474735

TRICHY I

Mobile : 9003075175

THRISSUR : Mobile : 9746474734

VUAYAWADA -Mubile : 9000005385 WEST

KOLHAPUR : Mobile : 8600992617

NASIK :

Mobile : 9730081553

GOA:

Mobile: 7757032203

SURAT : Mobile : 9724340890

BARODA ;

Mobile : 9205897978 CENTRAL

BILASPUR : Mobile : 9752593830

JABALPUR .

Mobile : 9752593831

GWALIOR :

Mobile : 9752593834

BHOPAL Mobile : 7389035949



INDIA'S NO. 1 TILE COMPANY

Kajaria Ceramics Limited

Corporate Office: J1/B1 (Extn.), Mohan Co - op Industrial Estate, Mathura Road, New Delhi - 110044, Ph.: +91-11-26946409, Fax: +91-11-26946407 Regd Office: 5F-11, Second Floor, JMD Regent Plaza, Mehrauli Gurgaon Road, Village Sikanderpur Ghosi, Gurgaon-122001, Haryana, Ph.: +91-0124-4081281 CIN No.: L26924HR1985PLC056150, E-mail: info@kajariaceramics.com, Web.: www.kajariaceramics.com