

PREMIUM
UNSANDED GROUT

Kajaria
TRANSFORM YOUR WORLD

For Joints 1mm to 3mm

Uniform Colour

Hard and Durable

High Water Resistant

Unsanded GROUT

Product Description:

Kajaria Unsanded Grout is a superior quality grout. It consist of a carefully prepared blend of white cement, chemical additives and fillers.

It is easy to install – just mix with water and use. It is an ideal for floors and walls in both exterior and interior applications.

Applications:

Used for filling tile joints with width 1mm to 3mm in both interior and exterior areas for ceramic & vitrified tiles.

Pack Size:

1 kg.

Shelf Life:

1 year in dry unopened pouches.

Advantages:

- Water resistant
- Improved stain resistance
- Improved efflorescence control
- Smooth & glossy finish
- Colour-fast
- Weather resistant
- Easy maintenance
- Non-shrinking
- Non-cracking
- Easy application and clean up

Coverage_(in sq. ft.): approximate coverage/10 Kg. grout


Tile Size x thickness (in mm)	1mm	2mm	3mm
100 x 100 x 3	1430	720	480
150 x 150 x 4	1610	810	540
200 x 150 x 5	1470	740	490
200 x 200 x 5	1720	860	570
200 x 300 x 6	1720	860	570
300 x 300 x 6	2150	1070	710
400 x 400 x 6	2860	1430	950
450 x 450 x 7	2760	1390	920
500 x 500 x 8	2680	1340	890
600 x 600 x 8	3210	1610	1070

Colours :

Plain



Brown



Chocolate



Copper Brown



Fiero



Autumn Yellow



Black



Ivory



Marble Beige



Rose



Almondo



Crema



Champagne



Granilia grey



Alpine Blue



Cobalt Blue



Steel Grey



Bottle Green



Aqua

Elite Plain



Turquoise Blue



Blanco Nieve

Method of Application:



Remove all Dust, Water, Oil & Sealers from Tile Surface with Scrubber.



Add 375* ml water in to bucket.



Add 1 Kg Grout in to water and mix it till attains Uniform Paste.



Slake the Material for 5 to 10 minutes.




Again Mix the material.



Fill the tile joints with Grout using a rubber float.



Remove the Excess Grout with help of rubber float.



Check for joints to harden 45 to 60 mins.



Take a wet scrubber.



Clean the Surface with wet scrubber.



Wait up to 24 Hrs.



After 24 Hrs you can allow the foot Traffic.

Kajaria Ceramics Limited

CORPORATE OFFICE :

J-1/B-1 (Extn.), Mohan Co-operative Industrial Estate, (Opp. Badar pur Thermal Power Station), Mathura Road, New Delhi - 110 044, INDIA Ph. : +91-11-26946409, Fax : +91-11-26946407

E-Mail : info@kajariaceramics.com, Website : www.kajariaceramics.com

Tollfree : 1800-11-2992